

# COLOR TOUCH-SCREEN DISPLAY



## PRINTER OPTION

A color Touch Screen display

### AN INTUITIVE GRAPHICAL INTERFACE

The new 2.4-inch color touch screen display lets you interact directly with the printer. This unique feature can be factory mounted or on-site upgrade.

The display, available in 16 languages, delivers information on the printer and consumables and allows to set some parameters (operating language, LCD settings, offsets, sleep mode, network settings).




---

**Target applications:**

- Banking
  - Transit
  - Loyalty
  - Casinos
- 

**Supported printers:**

- Primacy Expert
- Upon project request:  
Zenius  
Elypso

Compatible on printers produced from March 2013 (from SN: 10000295187)

This option is ideal for counter applications and operating environment without Evolis Premium Suite, requiring immediate printer information and reactivity to answer the printer's messages.

You can act quickly for the maintenance without having to be in front of the computer.

The diagnostics and the maintenance management are easy and intuitive.

### NOTIFICATIONS IN REAL TIME

All the printer's statuses are available permanently and displayed in real time and are easily understandable (color management):

- Notifications about the ribbon/cards level
- Ready to print (green color)
- Warning messages (orange color)
- Error messages (red color)

Localized management: you can relaunch or cancel a print job due to an error directly from the display for a convenient printer operation<sup>1</sup>.

Regular and advanced cleanings can be launched from the printer without the computer uses. A wizard on the display provides you the different steps.

By default, a buzzer warns you when:

- An error occurs
- During a print job, a warning message occurs.

Get a graphical touch screen interface for direct interaction with the printer for easier monitoring and operation.



<sup>1</sup> Evolis Premium Suite needs to be installed in Supervised or Standard Mode

# COLOR TOUCH SCREEN DISPLAY

## SPECIFICATIONS

<b>TYPE</b>	TFT-LCD color
<b>TOUCH</b>	Resistive
<b>RESOLUTION</b>	240 x 320 dpi, 16 bpp
<b>ACTIVE ZONE SIZE</b>	2.4 inches
<b>VIEW DIRECTION</b>	12 O'clock
<b>RAM</b>	16 MB
<b>ROM</b>	2 MB (Firmware) + 8 MB (Bitmap)
<b>REQUIREMENTS</b>	Compatible on printers produced from March 2013 (from SN: 10000295187) From X0x_USB_1614.firm From Evolis Premium Suite version: 6.22.0.838

## INTERFACE OPERATION

<b>LANGUAGES</b>	16 languages available: French, English, Italian, Spanish, German, Portuguese, Dutch, Polish, Turkish, Russian, Japanese, Simplified Chinese, Traditional Chinese, Korean, Farsi, Arabic.
<b>TYPE OF MESSAGES</b>	Informative, Warning and Error messages
<b>COLOR MANAGEMENT</b>	Green: OK – Ready Orange: warning alert Red: error alert – need to intervene to pursue print jobs.
<b>BUZZER</b>	2 beeps every 1 minute during 10 minutes until the problem is resolved Timing can be configured. Can be deactivated.

### EUROPE - MIDDLE EAST - AFRICA

Evolis  
14 avenue de la Fontaine – Z.I. Angers – Beaucouzé  
49070 Beaucouzé – France  
T +33 (0) 241 367 606 – F +33 (0) 241 367 612  
info@evolis.com

**AMERICAS** – Evolis Inc. – Fort Lauderdale – [evolisinc@evolis.com](mailto:evolisinc@evolis.com)

**ASIA-PACIFIC** – Evolis Asia Pte Ltd – Singapore – [evolisasia@evolis.com](mailto:evolisasia@evolis.com)

**CHINA** – Evolis China – Shanghai – [evolischina@evolis.com](mailto:evolischina@evolis.com)

**INDIA** – Evolis India – Mumbai – [evolisindia@evolis.com](mailto:evolisindia@evolis.com)